



 **watersportverbond**

T: 030 7513700

E: [info@watersportverbond.nl](mailto:info@watersportverbond.nl)

W: [www.watersportverbond.nl](http://www.watersportverbond.nl)

**CLASS RULES  
NATIONAL  
SPLASH RED  
CLASS  
2014**



**SPLASH RED**

7,2 m<sup>2</sup> new Flash Class

Effective Date : 1 may 2014  
Publication Date: : 28 may 2014  
previous edition :

The Splash Red is designed by Jac de Ridder and regonized as a National Class since 2014

# TABLE OF CONTENTS

---

## Table of contents

**INTRODUCTION** ..... 3

**SPLASH RED CLASS RULES** ..... 4

**C2 CREW** ..... 4

**C 10.3 IDENTIFICATION** ..... 4

**G3 MAINSAIL**..... 5

**G3.1 IDENTIFICATION** ..... 5

**G3.2 MATERIALS AND CONSTRUCTION** ..... 5

**G3.3 DIMENSIONS** ..... 6

## **Introduction**

The Splash Red is a National Class recognized by the Royal Dutch Yacht Federation. The boat and most parts of it are the same as for the Splash Blue. The mainsail and no age limit are the changes. Although the mainsail is also produced by the manufacturer. These Class Rules are a supplement to the Splash Blue Class rules and therefore the language is English and not Dutch.

This introduction only provides an informal background and the International Splash Red Class Rules proper begin on the next page.

PLEASE REMEMBER:

THESE RULES ARE CLOSED CLASS RULES WHERE IF IT DOES NOT SPECIFICALLY SAY THAT YOU MAY – THEN YOU SHALL NOT.

COMPONENTS, AND THEIR USE, ARE DEFINED BY THEIR DESCRIPTION.

## **Splash Red Class Rules**

The Splash Red Class Rules are valid from 2014, they will replace the existing Flash Class Rules after 2015.

Flash Class Rules are valid along with the Splash Red Class rules up to December 2015.

The pending International Splash Class Rules by ISAF are valid for Splash Red Class Rules with exclusion of the articles mentioned in the Splash Red Class Rules. The articles of the Splash Red Class Rules overrule the International Splash Class Rules with the same title/number.

**Following articles are valid for Splash Red Class Rules:**

### **C2 Crew**

- a. The **crew** shall consist of one person.
- b. There is no age limit on the Splash Red Class Rules.
- c. The **crew** shall be a current member of an NCA of SCIA or an individual member of SCIA when no NCA of SCIA exists in the country where the **crew** resides.
- d. While racing no part of the **crew** shall be positioned forward of the mast, except when the **boat** is capsized or for the time needed to haul in the painter, straighten the wind vane etc.

### **C 10.3 Identification**

- a. The national letters and **sail** numbers shall comply with the class rules.
- b. Rule C.10.3.a may be suspended in the case of charter boats at any event with the permission of the NCA of SCIA or SCIA Executive Committee.
- c. There is no difference in male or female crew in the **sail**, no Red Rhombus is required.
- d. No Red Rhombus is required.

## G3 Mainsail

### G3.1 Identification

- a. Identification on the **mainsail** shall comply with RRS except where amended by these **Class rules**.
- b. The class insignia shall be affixed on the starboard side in the panel below the top batten.  
The class insignia shall be:

Height	420 mm
Width	530 mm
Colour	Red
- c. The **sail** number shall be placed on both sides of the **sail**. The numbers shall be in the panel below the class insignia and below batten 2 from the top of the **sail**. The numbers on the starboard side shall be above the numbers on port side. The **sail** number displayed shall be the full number allocated to the **boat**.
- d. The **sail** numbers and nationality shall be in Red colour.

### G3.2 MATERIALS AND CONSTRUCTION

As per the building specification

### G3.3 DIMENSIONS

In addition to the requirements of the building specification the following dimensions may be checked.

	Minimum	Maximum
<b>Leech Length</b>	4850 mm	4910 mm
<b>Quarter width</b>	2075 mm	2105 mm
<b>Half width</b>	1635 mm	1665 mm
<b>Three-quarter width</b>	1065 mm	1095 mm
<b>Top width</b>	585 mm	615 mm
<b>Primary reinforcement from head and clew point</b>		320 mm
<b>Secondary reinforcement:</b>		
from <b>sail</b> corner measurement points		600 mm
for <b>batten pocket patches</b>		40 mm x 120 mm
<b>Window dimensions</b>		
<b>Window to sail edge</b>	260 mm	
Extension of headboard from <b>head point</b>	no <b>headboard</b>	no <b>headboard</b>
<b>Uppermost batten pocket length</b>		
Inside		975 mm
Outside		985 mm
<b>Intermediate and lower batten pocket length</b>		
Inside		635 mm
Outside		645 mm
<b>Uppermost batten pocket width</b>		
Inside		38 mm
Outside		70 mm
<b>Intermediate and lower batten pocket width</b>		
Inside		28 mm
Outside		40 mm
<b>Distance between intersection of leech and centreline of batten pockets</b>		
	1710 mm	1750 mm
<b>Clew point to intersection of leech pocket and centreline of lowermost batten</b>		
	1710 mm	1750 mm